

DERWENT-ACC-NO: 1988-106700
DERWENT-WEEK: 198816
COPYRIGHT 1999 DERWENT INFORMATION LTD

TITLE: Telecommunication exchange for teleprinters,
facsimile appts. etc. -
has differentiator assigned to memory to evaluate entered
communication and
send normal answer to sender if passed

INVENTOR: HAMADA, H; MYOJYO, T ; SHIMOMURA, Y ; TANIKAWA,
S

PATENT-ASSIGNEE: CANON KK[CANO]

PRIORITY-DATA: 1986JP-0237450 (October 6, 1986) ,
1986JP-0237446 (October 6,
1986) , 1986JP-0237447 (October 6, 1986) , 1986JP-0237448
(October 6, 1986)
, 1986JP-0237449 (October 6, 1986)

PATENT-FAMILY:

PUB-NO	PAGES	MAIN-IPC	PUB-DATE	LANGUAGE
DE 3733650 A	026	N/A	April 14, 1988	N/A
DE 3733650 C	000	N/A	December 12, 1991	N/A
JP 63090937 A	000	N/A	April 21, 1988	N/A
JP 63090938 A	000	N/A	April 21, 1988	N/A
JP 63090939 A	000	N/A	April 21, 1988	N/A
JP 63090940 A	000	N/A	April 21, 1988	N/A
JP 63090941 A	000	N/A	April 21, 1988	N/A

APPLICATION-DATA:

PUB-NO	APPL-DATE	APPL-DESCRIPTOR	APPL-NO
DE 3733650A		N/A	
1987DE-3733650		October 5, 1987	
JP63090937A		N/A	

1986JP-0237446	October 6, 1986
JP63090938A	N/A
1986JP-0237447	October 6, 1986
JP63090939A	N/A
1986JP-0237449	October 6, 1986
JP63090940A	N/A
1986JP-0237450	October 6, 1986

INT-CL (IPC): H04L011/20; H04L012/54 ; H04N001/21 ;
H04Q003/78

ABSTRACTED-PUB-NO: DE 3733650A

BASIC-ABSTRACT: The telecommunication system is connected to a number of terminals via transmission lines. The terminals are connected via a local network or can be installed at the same location. Likewise, the terminals can be connected via the local network or set up at the same location.

A memory (4) stores information passed from the terminals. A transmission device (3) sends the stored information to a predetermined terminal. A message is given, in a first step, from one terminal whose destination station is designated. In a second step, this message is held in the memory prior to assigning, in a third step, a terminal which is different from the destination station in the first step. In a fourth step, the stored message of the second step is transmitted to the terminal determined in the third step.

USE/ADVANTAGE - Allows message reception from terminals other than the designated terminal.

ABSTRACTED-PUB-NO: DE 3733650C

EQUIVALENT-ABSTRACTS: The communications system has entered video and text character data entered in a memory (4) before transmission to a remote peripheral, in response to control data received from the latter. The transceiver unit (3) has a decision circuit identifying

the stored data,
allowing the data to be transmitted to a corresponding
peripheral. Pref. the
communications system uses corresponding pairs of
facsimile and teleprinter
units. Each provides an identification code within the
transmitted code
signal. ADVANTAGE - Simple handling of different types
of data. (23pp)

CHOSEN-DRAWING: Dwg.3/17

TITLE-TERMS:

TELECOMMUNICATION EXCHANGE TELEPRINTER FACSIMILE
APPARATUS DIFFERENTIAL ASSIGN
MEMORY EVALUATE ENTER COMMUNICATE SEND NORMAL ANSWER SEND
PASS

DERWENT-CLASS: W01 W02

EPI-CODES: W01-A06X; W01-C02B; W01-C05B; W02-J09;

SECONDARY-ACC-NO:

Non-CPI Secondary Accession Numbers: N1988-080970